

# 4K Ultra HD Smart TV with Pro:Centric Direct









Pro:Centric Direct

4K UHD



UM670H Series

Design	Stand Type	65": 1 pole (Fixed) 55" / 50" / 43": 1 pole (Swivel)
Display	Sizes	65" / 55" / 50" / 43"
	Resolution	3,840 × 2,160 (4K UHD)
Broadcasting	Digital	ATSC, Clear QAM
System	Analog	NTSC
VESA	65" / 55": 300 50" / 43": 200	

#### UM670H Series



# **Pro:Centric Cloud**

Pro:Centric Cloud provides a convenient cloud-based environment for content management systems and other third-party software solutions that can be installed, updated and controlled from a central location. It also offers various design templates that provide eye-catching dashboards for analytics and data collection. In addition, the LG Channels app provides a convenient way to access a wide range of content from over-the-top channels (including broadcast TV) without additional devices or subscriptions. And LG's Mobile Application Creator simplifies the process of setting up concierge services on mobile devices for guests.



# **Pro:Centric Direct**

The Pro:Centric Direct hotel content management solution offers simple editing tools, making it easy to perform service and IP network-based remote management with a single click. Pro:Centric Direct enables users to customize their interface easily and efficiently manage all TVs in the facility. The most recent version\* provides IoT-based in-room control as well as voice control through LG Natural Language Processing.

\* Some features may not be supported based on PCD versions.



# Pro:Idiom

DRM (digital rights management) technology unlocks access to premium content to help assure rapid and broad deployment of HDTV and other high-value digital content. DRM technology also prevents any illegal copying of content.

#### UM670H Series



# Slim Depth for a Sleek Look

With a slim design, the UM670H series integrates smoothly with interiors, delivering a modern impression to your guests.



# Multi-code IR

Multi-code IR\* function eliminates any remote-control signal interaction between multiple TVs in one place. LG hospital TV supports this when used with the Multi-code IR remote control, so users can freely control their own TVs without disturbing the others.

\* Multi-code IR remote control is not provided by LG. (sold separately)



# SoftAP

Software-enabled Access Point\* (SoftAP) is a virtual Wi-Fi feature that uses TV as a wireless hotspot, enabling guests to connect their own devices to the SoftAP.

\* Screen Share may not be operated at the same time.




# Voice Recognition

Voice recognition, using the LG Magic Motion Remote\* with the UM670H Series makes it easy to control the TV without pressing the button of remote controls.

\* Magic Motion Remote is required (sold separately)

# CONNECTIVITY

# 65" / 55" / 50" / 43"



Side				
ME268755960 (#2400)	HDMI IN 2 (eARC/ARC) 3	Service Only	USB IN⊷↔ 1	RS-232CIN (CONTROL SPEAKER OUT & SERVICE)

#### UM670H Series

LUIT	ATIONS	65UM670H0UG	55UM670H0UA	50UM670H0UA	43UM670H0UA
Category	Category	Pro:Centric Smart	Pro:Centric Smart	Pro:Centric Smart	Pro:Centric Smart
	Diagonal	65"	55"	50"	43"
	Resolution	3,840 × 2,160 (UHD)	3,840 × 2,160 (UHD)	3,840 × 2,160 (UHD)	3,840 × 2,160 (UHD)
Display	Backlight Cabinet Type	Direct	Direct	Direct	Direct
	Brightness	330 nits	330 nits	330 nits	265 nits
	Dynamic Contrast Ratio	1,000,000:1	1,000,000:1	1,000,000:1	1,000,000:1
	Static (Panel) Contrast Ratio	1,200:1	1,300:1	5,000:1	1,200:1
	Response Time	8 ms (G to G)	14 ms (G to G)	19 ms (G to G)	8 ms (G to G)
	Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz
	Life Span	30,000 Hrs.	30,000 Hrs.	30,000 Hrs.	30,000 Hrs.
	Al Picture Pro	Yes	Yes	Yes	Yes
	Dynamic Vivid	Yes	Yes	Yes	Yes
Video	HDR 10 Pro / HDR HLG	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
	Game Optimizer	Yes	Yes	Yes	Yes
		10 W + 10 W	10 W + 10 W	10 W + 10 W	10 W + 10 W
	Speaker (Sound Output)				
A 11	Speaker System	2.0 ch	2.0 ch	2.0 ch	2.0 ch
Audio	Al Sound Pro / Al Sound	Yes	Yes	Yes	Yes
-	Al Acoustic Tuning	Yes (Ready)	Yes (Ready)	Yes (Ready)	Yes (Ready)
	LG Sound Sync	Optical/Bluetooth wireless	Optical/Bluetooth wireless	Optical/Bluetooth wireless	Optical/Bluetooth wireless
Broadcasting System	Digital (Terrestrial / Cable / Satellite)	ATSC, Clear QAM	ATSC, Clear QAM	ATSC, Clear QAM	ATSC, Clear QAM
	Analog (NTSC / SECAM / PAL)	NTSC	NTSC	NTSC	NTSC
	Global IPTV Support	Yes	Yes	Yes	Yes
Hospitality	Solution Type	Pro:Centric (Smart, Cloud, Direct, V)	Pro:Centric (Smart, Cloud, Direct, V)	Pro:Centric (Smart, Cloud, Direct, V)	Pro:Centric (Smart, Cloud, Direct,
		Vec	Yes	Yes	Vaa
Solution Smart Features	Mobile Co	Yes ice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF	Mode, Quick Access, Web Browser, SDI 7, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution	L P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake (	on RF, WOL,
Smart	webOS23 User Interfa Mobile Co Diagnostics External	L SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 O), In emote, Moving Picture Playback (SD/HD),	Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution 1, RS-232C), HTNG-CEC (1.4), Simplink (H rt Block, Welcome Screen (Splash Image stant On, VLAN ID, RIP (Remote Jack Pac (Plus HD), Auto Off / Sleep Timer, Energe	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake 4DMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (ł y Saving Mode, Motion Eye Care, <i>b</i> -LAN	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 1DMI-CEC),
Smart Features Hospitality	webOS23 User Interfa Mobile Co Diagnostics External	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAn nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo	Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution 1, RS-232C), HTNG-CEC (1.4), Simplink (H ert Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac (Plus HD), Auto Off / Sleep Timer, Energe ck, Credenza/Security Aperture (Except	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake 4DMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (ł y Saving Mode, Motion Eye Care, <i>b</i> -LAN	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 10MI-CEC), embedded
Smart Features Hospitality	webOS23 User Interfa Mobile Co Diagnostics External Mobile Re	ice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAl nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD) Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB	Mode, Quick Access, Web Browser, SDI P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution P, RS-232C), HTNG-CEC (1.4), Simplink (F ort Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac (Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spec DMI In (2.0), USB In (2.0), Antenna/Cable	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake e HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (H y Saving Mode, Motion Eye Care, <i>b</i> -LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv	u ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) HDMI-CEC), embedded ice Only (3.5 mm TRS) ut,
Smart Features Hospitality Features Jack	webOS23 User Interfa Mobile Co Diagnostics External Mobile Re Set Side Set Rear	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAl nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Po Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB	Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution II, RS-232C), HTNG-CEC (1.4), Simplink (H ort Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac (Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spea OMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) ( <i>b</i> -LAN Service),	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink ( y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 10MI-CEC), embedded ice Only (3.5 mm TRS) ut, 12)
Smart Features Hospitality Features Jack	webOS23 User Interfa Mobile Co Diagnostics External Mobile Re Set Side Set Rear VESA Compatible	ice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB	Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (H ort Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spea DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) ( <i>b</i> -LAN Service), 300 × 300 mm	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink ( y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) HDMI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm
Smart Features Hospitality Features Jack	webOS23 User Interfa Mobile Co Diagnostics External Mobile Re Set Side Set Rear VESA Compatible Stand Type	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB	Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (H ert Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spec- MI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) ( <i>b</i> -LAN Service), I 300 × 300 mm 1 pole (Swivel)	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (F y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e: In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel)	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) HDMI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel)
Smart Features Hospitality Features Jack	webOS23 User Interfa Mobile Co Diagnostics External Mobile Re Set Side Set Rear VESA Compatible Stand Type Front Color	ice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 300 × 300 mm 1 pole (Fixed) Dark Charcoal Gray	Mode, Quick Access, Web Browser, SD , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution , RS-232C), HTNG-CEC (1.4), Simplink (H ert Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spec DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) ( <i>b</i> -LAN Service), 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink ( y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 10MI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray
Smart Features Hospitality Features Jack	webOS23 User Interfa Mobile Co Diagnostics External Mobile Re Set Side Set Rear VESA Compatible Stand Type Front Color Dimensions without Stand (W x H x D)	ce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAl nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD, Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33 x 2.3 in. 1,454 × 838 x 57.7 mm	Mode, Quick Access, Web Browser, SDI P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution N, RS-232C), HTNG-CEC (1.4), Simplink (F ort Block, Welcome Screen (Splash Imagestant On, VLAN ID, RJP (Remote Jack Pace Plus HD), Auto Off / Sleep Timer, Energe ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spear MI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) ( <i>b</i> -LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 28.1 x 2.3 in. 1,235 × 715 × 57.5 mm	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake e HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink († y Saving Mode, Motion Eye Care, <i>b</i> -LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv el n (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RI 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 1DMI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm
Smart Features Hospitality Features Jack	webOS23 User Interfa Mobile Co Diagnostics External Mobile Re Set Side Set Rear VESA Compatible Stand Type Front Color Dimensions without Stand (W x H x D) Dimensions with Stand	ice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Mf Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33 x 2.3 in. 1,454 × 838 × 57.7 mm 57.2 x 35.8 x 13.4 in.	Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (H errt Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spec- MI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) ( <i>b</i> -LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 × 30.6 × 11.9 in.	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM cK) Compatibility (Teleadapt/Guestlink (F y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e: In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,221 × 651 × 57.1 mm 44.1 x 28.1 x 11.9 in.	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) HDMI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in.
Smart Features Hospitality Features Jack	webOS23 User Interfa Mobile Co Diagnostics External Mobile Re Set Side Set Rear VESA Compatible Stand Type Front Color Dimensions without Stand (W x H x D) Dimensions with Stand (W x H x D) Shipping Dimensions	cce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAl nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD) Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33 x 2.3 in. 1,454 × 838 × 57.7 mm 57.2 x 35.8 x 13.4 in. 1,454 × 909 × 340 mm 63 x 38.2 x 9 in.	Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution N, RS-232C), HTNG-CEC (1.4), Simplink (F ort Block, Welcome Screen (Splash Imagestant On, VLAN ID, RJP (Remote Jack Pace Plus HD), Auto Off / Sleep Timer, Energe ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Speci- In (2.0), RS-232C In (3.5 mm TRRS), Speci- Im (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) ( <i>b</i> -LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 28.1 x 2.3 in. 1,235 × 715 × 57.5 mm 48.6 x 30.6 x 11.9 in. 1,235 × 777 × 303 mm 53.5 x 33.9 x 8.1 in.	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (ł y Saving Mode, Motion Eye Care, <i>b</i> -LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RI 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 × 713 × 303 mm 51.9 x 31.9 x 7.4 in.	Dompatibility (MR18HA), Dom RF, WOL, Multi-code IR 1) HDMI-CEC), embedded 12 12 10 10 10 10 10 10 10 10 10 10
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand         (W x H x D)         Dimensions with Stand         (W x H x D)         Shipping Dimensions         (W x H x D)	cce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAl nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD) Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33 x 2.3 in. 1,454 × 838 × 57.7 mm 57.2 x 35.8 x 13.4 in. 1,454 × 909 × 340 mm 63 x 38.2 x 9 in. 1,600 × 970 × 228 mm	Mode, Quick Access, Web Browser, SDI P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution N, RS-232C), HTNG-CEC (1.4), Simplink (F ort Block, Welcome Screen (Splash Imagestant On, VLAN ID, RIP (Remote Jack Pace Plus HD), Auto Off / Sleep Timer, Energe ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spean MI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) ( <i>b</i> -LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 28.1 x 2.3 in. 1,235 × 715 × 57.5 mm 48.6 x 30.6 x 11.9 in. 1,235 × 777 × 303 mm 53.5 x 33.9 x 8.1 in. 1,360 × 860 × 207 mm	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake of HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM cK) Compatibility (Teleadapt/Guestlink (ł y Saving Mode, Motion Eye Care, <i>b</i> -LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv el n (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RI 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 × 713 × 303 mm 51.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 1DMI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 x 22.2 x 2.2 in. 967 × 564 × 57.1 mm 38.1 x 24.5 x 11.9 in. 967 × 654 × 57.1 mm 38.1 x 24.5 x 30 mm 42.3 x 26 x 8.0 in. 1,075 × 660 × 203 mm
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand (W x H x D)         Dimensions with Stand (W x H x D)         Shipping Dimensions (W x H x D)         Shipping themsions         (W x H x D)         Weight without Stand	cce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD) Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB TV- 300 × 300 mm 1 pole (Fixed) Dark Charcoal Gray 57.2 × 33 × 2.3 in. 1,454 × 838 × 57.7 mm 57.2 × 33.8 × 13.4 in. 1,454 × 909 × 340 mm 63 × 38.2 × 9 in. 1,600 × 970 × 228 mm 47.4 lbs. / 21.5 kg	<ul> <li>Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution R, S-232C), HTNG-CEC (1.4), Simplink (F ort Block, Welcome Screen (Splash Imagestant On, VLAN ID, RJP (Remote Jack Pace Plus HD), Auto Off / Sleep Timer, Energe ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spear MI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (<i>b</i>-LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 28.1 x 2.3 in. 1,235 × 715 × 57.5 mm 48.6 x 30.6 x 11.9 in. 1,235 × 777 × 303 mm 5.35 x 33.9 x 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg</li> </ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM cK) Compatibility (Teleadapt/Guestlink (ł y Saving Mode, Motion Eye Care, <i>b</i> -LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,221 × 651 x 57.1 mm 44.1 x 28.1 x 11.9 in. 1,211 × 713 × 303 mm 51.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg	Dompatibility (MR18HA), Dom RF, WOL, Multi-code IR 1) 1DMI-CEC), embedded 1ce Only (3.5 mm TRS) 1 pole (Swivel) 1 pole (Swivel) 1 pole (Swivel) 1 pole (Swivel) 0 Dark Charcoal Gray 38.1 x 22.2 x 2.2 in. 967 x 564 x 57.1 mm 38.1 x 24.5 x 11.9 in. 967 x 623 x 303 mm 42.3 x 26 x 8.0 in. 1,075 x 660 x 203 mm 19.4 lbs. / 8.8 kg
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand         (W x H x D)         Shipping Dimensions         (W x H x D)         Shipping Dimensions         (W x H x D)         Weight without Stand         Weight with Stand         Weight with Stand	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB S00 × 300 mm 1 pole (Fixed) Dark Charcoal Gray 57.2 x 35.8 x 13.4 in. 1,454 × 909 × 340 mm 63 x 38.2 x 9 in. 1,600 × 970 × 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg	<ul> <li>Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution ), RS-232C), HTNG-CEC (1.4), Simplink (H ort Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pack Plus HD), Auto Off / Sleep Timer, Energe ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spear (In (2.0), RS-232C In (3.5 mm TRRS), Spear MI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (<i>b</i>-LAN Service), 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6x 28.1x 2.3 in. 1,235 × 715 × 57.5 mm 48.6s 30.6x 11.9 in. 1,235 × 777 × 303 mm 53.5x 33.9 × 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg</li> </ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink ( y Saving Mode, Motion Eye Care, <i>b</i> -LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 27.1 mm 44.1 x 28.1 x 11.9 in. 1,121 × 615 x 57.1 mm 51.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg	Dompatibility (MR18HA), ompatibility (MR18HA), Multi-code IR 1) 10MI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 24.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 623 × 303 mm 42.3 × 26 × 8.0 in. 1,075 × 660 × 203 mm 19.4 lbs. / 8.8 kg 26.5 lbs. / 12.0 kg
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand         (W x H x D)         Shipping Dimensions         (W x H x D)         Shipping Dimensions         (W x H x D)         Shipping Wight without Stand         Weight with Stand         Shipping Weight	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Mf Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB TV- 300 × 300 mm 1 pole (Fixed) Dark Charcoal Gray 57.2 × 33 × 2.3 in. 1,454 × 909 × 340 mm 63 × 38.2 × 9 in. 1,600 × 970 × 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg 63.7 lbs. / 28.9 kg	<ul> <li>Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution ), RS-232C), HTNG-CEC (1.4), Simplink (H stant On, VLAN ID, RJP (Remote Jack Pac (Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spear OMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service), 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 28.1 x 2.3 in. 1,235 × 715 × 57.5 mm 48.6 x 30.6 x 11.9 in. 1,235 × 717 × 303 mm 53.5 x 33.9 x 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg</li> </ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (f y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 × 713 × 303 mm 51.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg	ompatibility (MR18HA),           on RF, WOL,           Multi-code IR           1)           HOMI-CEC),           embedded           ice Only (3.5 mm TRS)           ut,           12)           200 × 200 mm           1 pole (Swivel)           Dark Charcoal Gray           38.1 x 22.5 x 1.1 9 in.           967 × 564 × 57.1 mm           38.1 x 24.5 x 1.1 9 in.           1,075 × 660 × 203 mm           19.4 lbs. / 8.8 kg           26.5 lbs. / 12.0 kg           34.0 lbs. / 15.4 kg
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External:         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand (W x H x D)         Dimensions with Stand (W x H x D)         Shipping Dimensions (W x H x D)         Weight without Stand         Weight with Stand         Shipping Weight         On Bezel Width (L/R/U/B)	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB S00 × 300 mm 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33 x 2.3 in. 1,454 × 909 × 340 mm 63 x 38.2 x 9 in. 1,600 × 970 × 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg 63.7 lbs. / 28.9 kg 12.8 / 12.8 / 12.8 / 19.9 mm	<ul> <li>Mode, Quick Access, Web Browser, SDI , Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution ), RS-232C), HTNG-CEC (1.4), Simplink (F ert Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac (Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spear DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (<i>b</i>-LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 30.6 x 11.9 in. 1,235 × 715 × 57.5 mm 48.6 x 30.6 x 11.9 in. 1,236 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 12.8 / 12.9 mm</li> </ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink ( y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e), Inbut Charlon (1.5 mm Stereo), Serv e) (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 × 615 × 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 × 713 × 303 mm 5.1.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 2.6.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 12.9 mm	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 10MI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 623 × 303 mm 42.3 × 26 × 8.0 in. 1,075 × 660 × 203 mm 19.4 lbs. / 8.8 kg 26.5 lbs. / 12.0 kg 34.0 lbs. / 15.4 kg 12.8 / 12.8 / 12.8 / 19.9 mm
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand (W x H x D)         Dimensions with Stand (W x H x D)         Shipping Dimensions (W x H x D)         Weight without Stand         Weight with Stand         Shipping Weight         On Bezel Width (L/R/U/B)         Off Bezel Width (L/R/U/B)	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 35.8 x 13.4 in. 1,454 x 909 x 340 mm 63 x 38.2 x 9 in. 1,600 x 970 x 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg 63.7 lbs. / 28.9 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.8 / 6.8 / 6.8 / 18.4 mm	<ul> <li>Mode, Quick Access, Web Browser, SDI, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (H ert Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spec- DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (<i>b</i>-LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 20.6 x 11.9 in. 1,235 × 715 × 57.5 mm 48.6 x 30.6 x 11.9 in. 1,235 × 777 × 303 mm 53.5 x 33.9 x 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm</li> </ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (f y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e: In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 × 713 × 303 mm 5.1.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 2.6.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 10MI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 22. × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 623 × 303 mm 42.3 × 26 × 80 in. 1,075 × 660 × 203 mm 19.4 lbs. / 8.8 kg 26.5 lbs. / 12.0 kg 34.0 lbs. / 15.4 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand         (W x H x D)         Dimensions with Stand         (W x H x D)         Weight without Stand         (W x H x D)         Weight with Stand         On Bezel Width (L/R/U/B)         Off Bezel Width (L/R/U/B)         Power Supply (Voltage, Hz)	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33.2 x 3in. 1,454 x 909 x 340 mm 63 x 38.2 x 9 in. 1,600 x 970 x 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg 63.7 lbs. / 28.9 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.8 / 6.8 / 6.8 / 18.4 mm 100-240 Vac, 50/60 Hz	<ul> <li>Mode, Quick Access, Web Browser, SDI, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (Hart, RS-232C), HTNG-CEC (1.4), Simplink (Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spectra (Stant On, VLAN ID, RIP (Remote Jack Pac (Plus HD), Auto Off / Sleep Timer, Energy Ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spectra (Stant), Spectra (Sta</li></ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d IDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (F y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e) In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1x 28.1x 11.9 in. 1,121 × 713 × 303 mm 51.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) HDMI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 263 × 303 mm 42.3 × 26 × 8.0 in. 1,075 × 660 × 203 mm 19.4 lbs. / 8.8 kg 2.6.5 lbs. / 12.0 kg 34.0 lbs. / 15.4 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm 100-240 Vac, 50/60 Hz
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand (W x H x D)         Dimensions with Stand (W x H x D)         Shipping Dimensions (W x H x D)         Weight without Stand         Weight with Stand         Shipping Weight         On Bezel Width (L/R/U/B)         Off Bezel Width (L/R/U/B)	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 35.8 x 13.4 in. 1,454 x 909 x 340 mm 63 x 38.2 x 9 in. 1,600 x 970 x 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg 63.7 lbs. / 28.9 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.8 / 6.8 / 6.8 / 18.4 mm	<ul> <li>Mode, Quick Access, Web Browser, SDI, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (H ert Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Pac Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spec- DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (<i>b</i>-LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 20.6 x 11.9 in. 1,235 × 715 × 57.5 mm 48.6 x 30.6 x 11.9 in. 1,235 × 777 × 303 mm 53.5 x 33.9 x 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm</li> </ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (f y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e: In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 × 713 × 303 mm 5.1.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 2.6.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 10MI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 623 × 303 mm 42.3 × 26 × 8.0 in. 1,075 × 660 × 203 mm 19.4 lbs. / 8.8 kg 26.5 lbs. / 12.0 kg 34.0 lbs. / 15.4 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand         (W x H x D)         Dimensions with Stand         (W x H x D)         Weight without Stand         (W x H x D)         Weight with Stand         On Bezel Width (L/R/U/B)         Off Bezel Width (L/R/U/B)         Power Supply (Voltage, Hz)	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33.2 x 3in. 1,454 x 909 x 340 mm 63 x 38.2 x 9 in. 1,600 x 970 x 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg 63.7 lbs. / 28.9 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.8 / 6.8 / 6.8 / 18.4 mm 100-240 Vac, 50/60 Hz	<ul> <li>Mode, Quick Access, Web Browser, SDI, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (Hart, RS-232C), HTNG-CEC (1.4), Simplink (Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spectra (Stant On, VLAN ID, RIP (Remote Jack Pac (Plus HD), Auto Off / Sleep Timer, Energy Ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spectra (Stant), Spectra (Sta</li></ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d IDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (F y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e) In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1x 28.1x 11.9 in. 1,121 × 713 × 303 mm 51.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) HDMI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 263 × 303 mm 42.3 × 26 × 8.0 in. 1,075 × 660 × 203 mm 19.4 lbs. / 8.8 kg 2.6.5 lbs. / 12.0 kg 34.0 lbs. / 15.4 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm 100-240 Vac, 50/60 Hz
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand         (W x H x D)         Dimensions with Stand         (W x H x D)         Shipping Dimensions         (W x H x D)         Weight without Stand         Weight with Stand         Shipping Weight         On Bezel Width (L/R/U/B)         Power Supply (Voltage, Hz)         Power Consumption (Typ. / Max.)	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MF Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33 x 2.3 in. 1,454 × 838 × 57.7 mm 57.2 x 35.8 x 13.4 in. 1,454 × 899 × 340 mm 63 x 38.2 v 9 in. 1,600 × 970 × 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg 63.7 lbs. / 22.9 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.8 / 6.8 / 6.8 / 18.4 mm 100-240 Vac, 50/60 Hz 144 W / 180 W	<ul> <li>Mode, Quick Access, Web Browser, SDI, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (Hart Block, Welcome Screen (Splash Imagestant On, VLAN ID, RJP (Remote Jack Pac Plus HD), Auto Off / Sleep Timer, Energy ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spectra (1.2, 1.2, 1.2, 1.2, 1.2, 1.2, 1.2, 1.2,</li></ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d IDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (Fy Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1x 28.1x 11.9 in. 1,121 × 713 × 303 mm 51.9x 31.9x 7.4 in. 1,317 × 810 × 188 mm 2.6.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz 112 W / 135 W	ompatibility (MR18HA), on RF, WOL, Multi-code IR 1) 10MI-CEC), embedded ice Only (3.5 mm TRS) ut, 12) 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 564 × 50.1 mm 42.3 × 26 × 8.0 in. 1,075 × 660 × 203 mm 19.4 lbs. / 8.8 kg 26.5 lbs. / 12.0 kg 34.0 lbs. / 15.4 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm 100-240 Vac, 50/60 Hz 82 W / 119 W
Smart Features Hospitality Features Jack Interface	webOS23 User Interfa         Mobile Co         Diagnostics         External         Mobile Re         Set Side         Set Rear         VESA Compatible         Stand Type         Front Color         Dimensions without Stand         (W x H x D)         Dimensions with Stand         (W x H x D)         Shipping Dimensions         (W x H x D)         Weight without Stand         Weight with Stand         Shipping Weight         On Bezel Width (L/R/U/B)         Off Bezel Width (L/R/U/B)         Power Consumption (Typ. / Max.)         Standby Power Consumption	Lice, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (M Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HDMI In x2 (2.0), USB 1 pole (Fixed) Dark Charcoal Gray 57.2 x 33 x 2.3 in. 1,454 × 838 × 57.7 mm 57.2 x 35.8 x 13.4 in. 1,454 × 838 × 57.7 mm 57.2 x 35.8 x 13.4 in. 1,454 × 909 × 340 mm 63.3 88.2 v 9in. 1,600 × 970 × 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg 63.7 lbs. / 28.9 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.8 / 6.8 / 6.8 / 18.4 mm 100-240 Vac, 50/60 Hz 144 W / 180 W Under 0.5 W	<ul> <li>Mode, Quick Access, Web Browser, SDI, ,Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution I, RS-232C), HTNG-CEC (1.4), Simplink (H art Block, Welcome Screen (Splash Image stant On, VLAN ID, RJP (Remote Jack Parg protection), RSP-232C In (3.5 mm TRRS), Speci- ret Block, Welcome Screen (Splash Image ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Speci- MI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (<i>b</i>-LAN Service), I 300 × 300 mm 1 pole (Swivel) Dark Charcoal Gray 48.6 x 28.1 x 2.3 in. 1,235 × 715 × 57.5 mm 48.6 x 28.1 x 2.3 in. 1,235 × 717 × 303 mm 53.5 x 33.9 x 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm 100-240 Vac, 50/60 Hz 135 W / 163 W Under 0.5 W     </li> </ul>	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake d HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (Ir y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv e In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RI 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 × 651 × 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 × 713 × 303 mm 51.9 x 31.9 x 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz 112 W / 135 W Under 0.5 W	ompatibility (MR18HA),           on RF, WOL,           Multi-code IR           1)           HDMI-CEC),           embedded           ice Only (3.5 mm TRS)           ut,           12)           200 × 200 mm           1 pole (Swivel)           Dark Charcoal Gray           38.1 x 22.2 x 2.2 in.           967 x 653 x 303 mm           42.3 x 26x 8.0 in.           1,075 × 660 × 203 mm           19.4 lbs. / 8.8 kg           26.5 lbs. / 12.0 kg           34.0 lbs. / 15.4 kg           12.8 / 12.8 / 12.8 / 19.9 mm           6.9 / 6.9 / 6.9 / 18.4 mm           100-240 Vac, 50/60 Hz           82 W / 119 W           Under 0.5 W

\* Specifications are subject to change without notice. Please make sure to check the product manual for details about product usage.

https://www.lg.com/us/business/commercial-display
 https://www.youtube.com/lgcommercialdisplayusa
 https://www.facebook.com/LGcommercialdisplays
 https://www.linkedin.com/company/lg-commercial-displays-usa
 https://www.twitter.com/LGCommDisplays

Copyright 2023 <sup>®</sup>LG Electronics USA, Inc., 2000 Millbrook Drive Lincolnshire, IL 60069, USA. All rights reserved. LG and the LG logo are registered trademarks of LG Corp. All other products and brand names are trademarks or registered trademarks of their respective companies. Designs, features, and specifications are subject to change without notice. All screen images are simulated. LG\_SPEC-SHEET\_UM670H\_0723SK\_LR.pdf



